Document

Select the documents you wish to save or order by clicking the box next to the document, or click the link above the document to order directly.

save locally as: PDF document search strategy: do not include the search strategy

previous documents order

Results from INSPEC search of "measurement" AND parasitic ADJ Inductance"

☑ Select All

4 Analysis and measurement of small inductance of loops and vias on printed
16 Characteristic-impedance measurement error on lossy substrates.
26 Nanohenry inductance measurement using a low parasitic-inductance probe.
27 Nanohenry inductance measurement using a low-parasitic-inductance- probe.
28 Sub-nanohenry inductance measurement using a zero-parasitic-inductance probe
30 Characterizing IC packages and interconnects.
45 Measurement of parasitic inductance of capacitors.

☑ **document 4 of 45** Order Document

Ordered on 5/19

5 articles ordered.

INSPEC - 1969 to date (INZZ)

Accession number & update
8031736, B2004-08-2210B-007; 20040718.

Title
Analysis and **measurement** of small **inductance** of loops and vias on printed circuit board.

Author(s)
Yang-Chen; Guozhu-Chen; Smedley-K.

Author affiliation
Dept of Electr Eng & Comput Sci, California Univ, Irvine, CA, USA.

Source
IECON'03. 29th Annual Conference of the IEEE Industrial Electronics Society, Vol.2, Roanoke, VA, USA, 2-6 Nov. 2003.
Sponsors: IEEE Industrial Electronics Soc.
In: p.1661-6 Vol.2, 2003.

ISSN
ISBN: 0-7803-7906-3, CCCC: 0-7803-7906-3/03/ ($17.00).

Publication year
2003.

Language
EN.

Publication type
CPP Conference Paper.

Treatment codes
T Theoretical or Mathematical; X Experimental.

Abstract
Printed circuit board (PCB) design has become a crucial issue for high density packaging of power electronics circuits. The traces, loops and vias on the PCB all introduce **parasitic inductance,** which causes high frequency ringing in the circuit and thus additional losses. In this paper, the **inductance** of several typical loops and vias on PCB is analyzed using Neumann formula. Studies show that the **self-**

inductance of the rectangular loop is related to the length/width ratio, the trace width as well as the rectangular area. The mutual **inductance** between two loops is related to their relative position as well as their common area. When a loop contains vias, they may introduce additional **inductance** due to the additional cross-sectional area formed by the vias, while the vias themselves have little contribution to the **inductance** in the switching frequency domain. A simple and accurate test circuit was built based on oscillation method to measure the small **inductance** of loops on the PCB. Experimental results match the theoretical prediction with acceptable errors. Finally, some useful design guidelines are presented to optimize the layouts. (6 refs).

Descriptors

circuit-oscillations; inductance-measurement; power-electronics; printed-circuit-design.

Keywords

printed circuit board design; high density packaging; power electronics circuits; traces; loops; vias; oscillation method; **inductance measurement;** Neumann formula.

Classification codes

B2210B (Printed circuit layout and design).
B2560P (Power semiconductor devices).
B2570P (Power integrated circuits).
B7310J (Impedance and admittance measurement).

☑ **document 16 of 45** Order Document

INSPEC - 1969 to date (INZZ)

Accession number & update

6996465, B2001-09-7310J-004; 20010730.

Title

Characteristic-impedance **measurement** error on lossy substrates.

Author(s)

Williams-D-F; Arz-U; Grabinski-H.

Author affiliation

Nat Inst of Stand & Technol, Boulder, CO, USA.

Source

IEEE-Microwave-and-Wireless-Components-Letters (USA), vol.11, no.7, p.299-301, July 2001. , Published: IEEE.

CODEN

IMWCBJ.

ISSN

ISSN: 1531-1309, CCCC: 1531-1309/2001/ ($10.00).

Availability

SICI: 1531-1309(200107)11:7L.299:CIME; 1-Z
Electronic Journal Document Number: S1531-1309(01)05937-2.

Publication year

2001.

Language

EN.

Publication type

J Journal Paper.

Treatment codes
T Theoretical or Mathematical.
Abstract
This paper examines error caused by **parasitic inductance** in the characteristic impedance measured by the calibration comparison method on lossy silicon substrates. (13 refs).
Descriptors
calibration; electric-impedance-measurement; measurement-errors; microwave-measurement.
Keywords
characteristic impedance **measurement** error; **parasitic inductance;** calibration comparison method; lossy silicon substrate; Si.
Classification codes

```
B7310J    (Impedance and admittance measurement).
B7310N    (Microwave measurement techniques).
B7130     (Measurement standards and calibration).
```

Chemical indexing
Si sur, Si el.
Copyright statement

USPTO Full Text Retrieval Options

☑ **document 26 of 45** Order Document
INSPEC - 1969 to date (INZZ)



Accession number & update
5409621, B9612-7310J-006; 961029.
Title
Nanohenry **inductance measurement** using a low **parasitic-inductance** probe.
Author(s)
Shimizu-H; Nagata-T; Nakamura-A.
Author affiliation
Mech Eng Res Lab, Hitachi Ltd, Tsuchiura, Japan.
Source
Electronics-and-Communications-in-Japan-Part-2 (Electronics)(USA), vol.79, no.6, p.95-102, June 1996. , Published: Scripta Technica.
CODEN
ECJEEJ.
ISSN
ISSN: 8756-663X, CCCC: 8756-663X/96/0006-0095.
Availability
SICI: 8756-663X(199606)79:6L.95:NIMU; 1-Q.
Publication year
1996.
Language
EN.
Publication type
J Journal Paper.
Treatment codes
P Practical; X Experimental.
Abstract
The increased speeds of logic circuitry make the electrical characteristics of LSI packages more

important. This is especially true of **inductance,** which is the main source of simultaneous switching noise (SSN). To improve the accuracy of SSN simulations, **inductance** models of LSI packages should be represented by **inductance** matrices, and thus to construct precise models, it is necessary to have an **inductance measurement** method. A new **inductance measurement** method of nanohenry-order accuracy is proposed that uses an LCR-meter. Since the **parasitic inductance** of **measurement** probes usually decreases accuracy, a special probe with minimized **parasitic inductance** was developed. The new **measurement** method has the additional advantage of high spatial resolution. The results of measurements proved to be in good agreement with calculations. (7 refs).

Descriptors

inductance-measurement; integrated-circuit-modelling; integrated-circuit-noise; large-scale-integration; logic-design; probes.

Keywords

inductance measurement; low **parasitic inductance** probe; logic circuitry; electrical characteristics; LSI packages; **inductance;** simultaneous switching noise; SSN simulation; **inductance** models; **inductance** matrices; LCR meter; **parasitic inductance; measurement** probes; spatial resolution.

Classification codes

B7310J (Impedance and admittance measurement).
B1265B (Logic circuits).
B2570A (Integrated circuit modelling and process simulation).

USPTO Full Text Retrieval Options

☑ **document 27 of 45** Order Document

INSPEC - 1969 to date (INZZ)

Accession number & update

5197808, B9604-7310J-005; 960227.

Title

Nanohenry **inductance measurement** using a **low-parasitic-inductance-** probe.

Author(s)

Shimizu-H; Nagata-T; Nakamura-A.

Author affiliation

Mech Eng Res Lab, Hitachi Ltd, Tsuchiura, Japan.

Source

Transactions-of-the-Institute-of-Electronics-Information-and-Communication-Engineers-C-II (Japan), vol.J79C-II, no.1, p.8-14, Jan. 1996. , Published: Inst. Electron. Inf. & Commun. Eng.

CODEN

DCSOEF.

ISSN

ISSN: 0915-1907.

Availability

SICI: 0915-1907(199601)J79CII:1L.8:NIMU; 1-4.

Publication year

1996.

Language

JA.

Publication type

J Journal Paper.

Treatment codes
X Experimental.
Abstract
Increasing speeds of logic systems add importance to the electrical characterization of LSI packages especially characterization of **inductance** which is a main source of simultaneous switching noise (SSN). To improve the SSM simulation accuracy, **inductance** models of LSI packages should be represented by **inductance** matrices. To construct precise **inductance** models, it is desirable to have an **inductance measurement** method. A new **inductance measurement** method of nanohenry order is proposed using an LCR meter. Since **parasitic inductance** of probes usually decreases **measurement** accuracy, we developed a special probe to minimize such **parasitic inductance.** The new **measurement** method has special merits such as high spatial resolution. The results measured were proved to be in good agreement with simulation. (9 refs).
Descriptors
inductance-measurement; probes.
Keywords
parasitic inductance; nanohenry **inductance measurement;** LSI packages; simultaneous switching noise; probe; logic systems; LCR meter; spatial resolution; simulation.
Classification codes
B7310J (Impedance and admittance **measurement).**
Copyright statement

☑ **document 28 of 45** Order Document ✓ ordered
INSPEC - 1969 to date (INZZ)

Accession number & update
5170139, A9604-0750-009, B9603-7310J-003; 960123.
Title
Sub-nanohenry **inductance measurement** using a **zero-parasitic-inductance** probe system.
Author(s)
Nagata-T; Shimizu-H; Nakamura-A; Fukumoto-H.
Author affiliation
Mech Eng Res Lab, Hitachi Ltd, Ibaraki, Japan.
Source
1995 Proceedings. 45th Electronic Components and Technology Conference, Las Vegas, NV, USA, 21-24 May 1995.
In: p.337-42, 1995.
ISSN
ISBN: 0-7803-2736-5, CCCC: 0569-5503/95/0000-0337 ($3.00).
Publication year
1995.
Language
EN.
Publication type
CPP Conference Paper.
Treatment codes
N New Development; P Practical; X Experimental.
Abstract
A new **inductance measurement** method of a sub-nanohenry order is proposed using an LCR meter. Since **parasitic** inductances of probes usually decreases the **measurement** accuracy, we developed two types of special probes to minimize such **parasitic** inductances. The new **measurement** methods have special merits, such as separate measurements of each trace and a high spatial resolution. They also enable measurements of inductances not only for simple traces, but also for combined trace-and-sheet conductor systems. The results measured proved to be in good agreement with our electro-magnetic simulator. The eddy current effect was successfully demonstrated by using this method. (6

refs).

Descriptors

equivalent-circuits; inductance-measurement; measurement-errors; probes.

Keywords

sub nanohenry **inductance measurement;** zero **parasitic inductance** probe system; LCR meter; **parasitic inductance** minimisation; eddy current effect.

Classification codes

A0750 (Electrical instruments and techniques).
A0620D (Measurement and error theory).
B7310J (Impedance and admittance measurement).
B7110 (Measurement theory).

USPTO Full Text Retrieval Options

☑ **document 30 of 45** Order Document

INSPEC - 1969 to date (INZZ)

Accession number & update

4580332, B9403-0170J-004; 940120.

Title

Characterizing IC packages and interconnects.

Author(s)

Jones-K.

Author affiliation

Tektronix Inc, Beaverton, OR, USA.

Source

Test-Measurement-World (USA), vol.13, no.7, p.55-6, 58, 60, June 1993.

CODEN

TMWOD8.

ISSN

ISSN: 0744-1657.

Publication year

1993.

Language

EN.

Publication type

J Journal Paper.

Treatment codes

P Practical.

Abstract

Without question, IC packages and interconnects are the greatest obstacles to improving computer performance. Connection delays, not device speeds, are limiting the performance of today's high-speed computers. Edge speeds of digital ICs are now so fast you can no longer ignore the **parasitic inductance** and capacitance of IC interconnects. Measuring and modeling the characteristics of IC packages and interconnects will help you to increase the performance of your IC designs. (0 refs).

Descriptors

characteristics-measurement; digital-integrated-circuits; packaging.

Keywords

edge speeds; connection delays; IC packages; interconnects; computer performance; high speed

computers; digital ICs; **parasitic inductance;** capacitance.

Classification codes

B0170J (Product packaging).
B1265 (Digital electronics).

USPTO Full Text Retrieval Options

☑ **document 45 of 45** Order Document

INSPEC - 1969 to date (INZZ)

Accession number & update

43572, B69013037; 690000.

Title

Measurement of **parasitic inductance** of capacitors.

Source

Przeglad-Elektroniki (Poland), vol.10, no.1, p.42-43, 1969.

might take too long to order. skip

CODEN

PRELAX.

ISSN

ISSN: 0552-4172.

Publication year

1969.

Language

PO.

Publication type

J Journal Paper.

Descriptors

capacitors; inductance; inductance-measurement.

Classification codes

B2130 (Capacitors).
B7310J (Impedance and admittance).

print locally as: PDF document search strategy: do not include the search strategy

Previous document Order

Top - News & FAQS - Dialog